Technical Information



Replaces the Technical Information dated 17.05.99

KIWODUR ® 1001 HMT

Hardener for two-component screen adhesives of the KIWOBOND 1000 HMT series

KIWODUR 1001 HMT is a colourless hardener for the KIWOBOND 1000 HMT series. It is used if colourless adhesive layers are required. For details about application and properties please refer to the technical data sheet for the adhesive component.

BASIS Polyisocyanate, containing solvents

COLOUR Colourless to slightly brown, transparent

SOLIDS CONTENT Approx. 40%

DENSITY Approx. 1,03 g/cm³

FLASH POINT Approx. -4°C

HEALTH HAZARDS/ ENVIRONMENTAL PROTECTION KIWODUR 1001 HMT is quite thin fluid and may spatter when opening the can and pouring out the hardener, therefore necessarily wear suitable protective clothes and goggles, both when preparing and when applying the

product.

Please follow further information given in the material safety data sheet.

STORAGE 1 year (at 20 – 25°C in original container)

KIWODUR 1001 HMT is sensitive to humidity and must therefore be stored in the tightly closed original container. Avoid storage at higher temperatures.

This data sheet is for your information, a legally binding guarantee of the product's suitability for a particular application cannot be derived. No responsibility can be undertaken for occurring damages. Our products are subject to a continuous production and quality control and leave our factory in perfect condition.